

Minigator



Main Control Panel

Back By Popular Demand

Introducing the newest member of the Electrogator II family of high quality center pivots, the all-new Minigator. Equipped with 4.5" water pipe the Minigator still offers many of the same features as its big brother - the Electrogator II.

Reinke has been building and servicing this type of small piped machine since 1971 with many of the original Minigator machines still operating today - all around the world.

With a maximum system length of 1,300 feet and a simplified yet fully-functional, high-quality control panel standard, the Minigator is a perfect fit for small or irregularly shaped fields, pivot corners, low gallonage wells or simply where you need a lower cost system alternative.

For all the details about an irrigation system that is sized down for your smaller fields yet loaded up with Reinke's time proven Electrogator II features, benefits and quality you demand, see your local Reinke dealer today!!

To find your nearest Reinke dealer call our Grower's Hotline at (866) 365-7381 or go to www.reinke.com for our convenient dealer locator service.



Internal Hook & Receiver Connection



Collector Reel



5325 Reinke Road
Deshler, Nebraska 68340 U.S.A.
Ph. 402-365-7251 • Fax 402-365-4370
Grower's Hotline: 866-365-7381
e-mail: international@reinke.com
www.reinke.com

Minigator

System Specifications

Pivot Point	6" pivot center
Pipe Diameter	4.5"
Pipe Type	High strength galvanized steel with Reinke's industry exclusive V-ring seal construction
Outlet spacing	57"
Span lengths	118', 137', 156' and 175'
118' Span weight (lbs.) Wet	3,066 lbs.
137' Span weight (lbs.) Wet	3,248 lbs.
156' Span weight (lbs.) Wet	3,452 lbs.
175' Span weight (lbs.) Wet	3,906 lbs.
Span Connection	Reinke's standard internal hook and receiver
Truss Rods	High strength 9/16"
Truss Struts	2 1/8" x 2 1/8" 10 gauge and 12 gauge
Truss Cross Braces	1 3/4" x 1 3/4" 10 gauge
Tower Leg	Roll formed C-Channel 8" x 3" x 1.25"
Tower Height	Standard height minimum 9' crop clearance
Tower Box	Reinke's industry exclusive double walled tower box
Endboom Lengths	3', 13', 23', 32' and 42'
Booster Pump Option	2 HP
Available Tire Sizes	11 x 22.5", 11.2 x 24", 14.9 x 24", 11.2 x 38", 13.6 x 38"
Maximum Machine Length	1,300'
Drive Train	UMC Moderate Duty Wheel Gear or UMC 740
Single Phase	Yes / 220
Towable Pivot Point	Kwik tow
Main Control Panel	RPM Basic Panel standard with all levels of RPM panels available



Reinke
 MORE RIGHT THAN RAIN